

APPROVED FOR PUBLIC RELEASE
DISTRIBUTION UNLIMITED

AFPEA REPORT NO. 95-R-01
AFPEA PROJECT NO. 94-P-119

JASON M. GILREATH

Mechanical Engineer

DSN 787-3362
Comm. (513) 257-3362



Development of Handling Frames and Shipping Containers for
250AH Lithium Thionyl Chloride Batteries

AFMC LSO/LOP
PACKAGING BRANCH
5215 THURLOW ST BLDG 70
WRIGHT-PATTERSON AFB, OH 45433-5540
March 1995

19950629 010

DTIC QUALITY INSPECTED 5

NOTICE

When government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related government procurement operation, the United States Government thereby incurs no responsibility whatsoever, and the fact that the government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture use or sell any patented invention that may in any way be related thereto. This report is not to be used in whole or part for advertising or sales purposes.

PROJECT: 94-P-119
TITLE: 250AH Lithium Thionyl Chloride Battery Containers

ABSTRACT

The Martin-Marietta Corporation in conjunction with SAFT of France developed six batteries that needed to be shipped from Poitiers, France to Cape Canaveral, Florida in a very short time. The Aerospace Corporation was tasked with solving this problem. Aerospace designed a Lexan/Aluminum handling fixture that they believed would satisfy the requirements, but they needed assistance with the design of a container and cushioning system and fabrication of the fixtures. The Air Force Packaging Evaluation Activity (AFPEA) was asked to provide assistance.

Each battery had to be shipped separately inside an 85 gallon steel drum which was UN certified for shipment of hazardous materials. A polyethylene cushioning system was designed that would attenuate shock to 30 G's and a self-contained transport recorder that would measure shock and temperature accompanied each battery.

AFPEA fabricated and assembled the Lexan/Aluminum fixtures. Handle pull tests were also performed on the fixtures to provide Aerospace with the required assurances that their handling fixture would perform adequately.

MAN-HOURS: 150

PREPARED BY:

PUBLICATION DATE:


12 5 APR 1995

JASON M. GILREATH
Mechanical Engineer
AF Packaging Technology &
Engineering Facility



REVIEWED BY:

TED HINDS
Supervisor, Design Group
AF Packaging Technology &
Engineering Facility



APPROVED BY:

LESLIE K. CLARKE, III
Chief,
Packaging Branch




Accession For	
NTIS	CRA&I <input checked="" type="checkbox"/>
DTIC	TAB <input type="checkbox"/>
Unannounced <input type="checkbox"/>	
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
	

TABLE OF CONTENTS

	<u>PAGE</u>
Abstract	i
Table of Contents	ii
Introduction	1
Background	1
Requirements	1
Design	1
Configuration	1
Testing	1
Test Specimen	1
Test Plan	1
Test Results	2
Conclusion	2

APPENDICES

Appendix 1: Aerospace drawing SK 104-1.....	3
Appendix 2: Aerospace drawing SK 101.....	5
Appendix 3: Polyethylene cushion.....	8
Appendix 4: Test Plan/Results.....	10
Appendix 5: Distribution List.....	14
Appendix 6: Report Documentation.....	21

INTRODUCTION:

BACKGROUND:

The Martin-Marietta Corporation in conjunction with SAFT of France developed six batteries that needed to be shipped from Poitiers, France to Cape Canaveral, Florida in a very short time. These batteries contain an unusually large amount of Lithium, which is a hazardous material. Hazardous material shipment requires special attention to detail and safety. The Aerospace Corporation was tasked with solving this problem. Aerospace designed a Lexan/Aluminum handling fixture that they believed would satisfy the requirements, but they needed assistance with the design of a container and cushioning system and fabrication of the fixtures. The Air Force Packaging Evaluation Activity (AFPEA) was asked to provide assistance.

REQUIREMENTS:

AFPEA was to provide six deliverable sets of air cargo only transportation packaging for the 250AH Lithium Thionyl Chloride batteries as defined on the Aerospace Corporation drawing SK 104-1 (appendix 1) and its details. The packaging conforms to the Aerospace Corporation drawing SK 101 (appendix 2). The first setup was intended to ship an inert 'pathfinder' battery to ensure the shock and environmental requirements were being met. A self-contained transport recorder was attached to each fixture in order to record the shock and temperature data.

DESIGN:

CONFIGURATION:

The outer container is an 85 gallon steel drum that is UN certified for shipment of hazardous materials. The cushion (appendix 3) is made from laminated 2pcf polyethylene foam and is designed to attenuate shock levels to 30G's. The fixture to which the battery is bolted is made from a combination of GE Lexan, a high strength plastic, and aluminum plate and bar stock. Because the battery is transported at low temperatures and is loaded into the container at 0°F and must be kept as cold as possible during transit, the fixture and battery assembly is double bagged with shrink wrap, wrapped with Armaflex insulation, and then sealed inside a double-wall fiberboard box.

TESTING:

TEST SPECIMEN:

A concern was raised about the strength of the fixture handles. A handle pull test was conducted. AFPEA had fabricated enough parts to make seven complete fixtures, so there was no concern about damaging any critical parts. The test specimen was a complete fixture loaded with lead blocks (nominal 50 lb/ea).

TEST PLAN:

See appendix 4.

TEST RESULTS:

A handling fixture was loaded with lead weights totaling up to 600 lbs and hung free of support by both handles and also one single handle. In neither case did the handles fail or show signs of fracture.

CONCLUSION:

The pathfinder battery container was completed and shipped on schedule. Results from the transport recorder showed shock levels well below the required 30 G's. The remaining batteries were to be shipped as scheduled because of the positive results seen in the pathfinder.

There was, however, a concern as to whether or not the handles were strong enough to provide a factor of safety of 2. A test was run to demonstrate the handle strength. Although the plain Lexan handles easily passed the pull test (Appendix 4), the users were not satisfied with the 'feel' of that configuration. An aluminum reinforcement was designed and installed on the remaining five fixture assemblies. With the newly reinforced handles, the remaining fixtures and containers were shipped without incident, successfully leaving France and arriving at Cape Canaveral.

APPENDIX 1
AEROSPACE DRAWING SK 104-1

APPENDIX 2
AEROSPACE DRAWING SK 101

ZONE	TECH	DESCRIPTION	DATE	APPROVAL
03	A	1. ADDED ALYDDED COVER	10-30-84	6. DENNO
04		2. ADDED STEEL BRACE		
05		3. ADDED STEEL BRACE		
06		4. ADDED STEEL BRACE		
07		5. ADDED STEEL BRACE		
08		6. ADDED STEEL BRACE		
09		7. ADDED STEEL BRACE		
10		8. ADDED STEEL BRACE		
11		9. ADDED STEEL BRACE		
12		10. ADDED STEEL BRACE		
13		11. ADDED STEEL BRACE		
14		12. ADDED STEEL BRACE		
15		13. ADDED STEEL BRACE		
16		14. ADDED STEEL BRACE		
17		15. ADDED STEEL BRACE		
18		16. ADDED STEEL BRACE		
19		17. ADDED STEEL BRACE		
20		18. ADDED STEEL BRACE		
21		19. ADDED STEEL BRACE		
22		20. ADDED STEEL BRACE		
23		21. ADDED STEEL BRACE		
24		22. ADDED STEEL BRACE		
25		23. ADDED STEEL BRACE		
26		24. ADDED STEEL BRACE		
27		25. ADDED STEEL BRACE		
28		26. ADDED STEEL BRACE		
29		27. ADDED STEEL BRACE		
30		28. ADDED STEEL BRACE		
31		29. ADDED STEEL BRACE		
32		30. ADDED STEEL BRACE		
33		31. ADDED STEEL BRACE		
34		32. ADDED STEEL BRACE		
35		33. ADDED STEEL BRACE		
36		34. ADDED STEEL BRACE		
37		35. ADDED STEEL BRACE		
38		36. ADDED STEEL BRACE		
39		37. ADDED STEEL BRACE		
40		38. ADDED STEEL BRACE		
41		39. ADDED STEEL BRACE		
42		40. ADDED STEEL BRACE		
43		41. ADDED STEEL BRACE		
44		42. ADDED STEEL BRACE		
45		43. ADDED STEEL BRACE		
46		44. ADDED STEEL BRACE		
47		45. ADDED STEEL BRACE		
48		46. ADDED STEEL BRACE		
49		47. ADDED STEEL BRACE		
50		48. ADDED STEEL BRACE		
51		49. ADDED STEEL BRACE		
52		50. ADDED STEEL BRACE		
53		51. ADDED STEEL BRACE		
54		52. ADDED STEEL BRACE		
55		53. ADDED STEEL BRACE		
56		54. ADDED STEEL BRACE		
57		55. ADDED STEEL BRACE		
58		56. ADDED STEEL BRACE		
59		57. ADDED STEEL BRACE		
60		58. ADDED STEEL BRACE		
61		59. ADDED STEEL BRACE		
62		60. ADDED STEEL BRACE		
63		61. ADDED STEEL BRACE		
64		62. ADDED STEEL BRACE		
65		63. ADDED STEEL BRACE		
66		64. ADDED STEEL BRACE		
67		65. ADDED STEEL BRACE		
68		66. ADDED STEEL BRACE		
69		67. ADDED STEEL BRACE		
70		68. ADDED STEEL BRACE		
71		69. ADDED STEEL BRACE		
72		70. ADDED STEEL BRACE		
73		71. ADDED STEEL BRACE		
74		72. ADDED STEEL BRACE		
75		73. ADDED STEEL BRACE		
76		74. ADDED STEEL BRACE		
77		75. ADDED STEEL BRACE		
78		76. ADDED STEEL BRACE		
79		77. ADDED STEEL BRACE		
80		78. ADDED STEEL BRACE		
81		79. ADDED STEEL BRACE		
82		80. ADDED STEEL BRACE		
83		81. ADDED STEEL BRACE		
84		82. ADDED STEEL BRACE		
85		83. ADDED STEEL BRACE		
86		84. ADDED STEEL BRACE		
87		85. ADDED STEEL BRACE		
88		86. ADDED STEEL BRACE		
89		87. ADDED STEEL BRACE		
90		88. ADDED STEEL BRACE		
91		89. ADDED STEEL BRACE		
92		90. ADDED STEEL BRACE		
93		91. ADDED STEEL BRACE		
94		92. ADDED STEEL BRACE		
95		93. ADDED STEEL BRACE		
96		94. ADDED STEEL BRACE		
97		95. ADDED STEEL BRACE		
98		96. ADDED STEEL BRACE		
99		97. ADDED STEEL BRACE		
100		98. ADDED STEEL BRACE		

COMPLIES WITH CODE OF FEDERAL REGULATIONS
TITLE 49

SHIPPING DESIGNATIONS
PROPER SHIPPING NAME: LITHIUM BATTERY,
LIQUID CATHODE

UN NUMBER: 3090
HAZARD CLASS: 9
PACKING GROUP: II

1. TWO STEEL BANDS
1 1/2" TO 3/4" X 0.020
UNDER TOP PALLET BOARDS ONLY

28.5 IN X 28.5 IN
X 0.5 IN PLYWOOD

40 IN X 48 IN PALLET

48 IN MAX

4. FOR TRANSPORT OF DAMAGED OR DISCREPANT LITHIUM BATTERY. SEE SK 120

3. DEFINES ASSEMBLY FOR TRANSPORT EMPTY OR LOADED WITH
ACCEPTABLE LITHIUM BATTERY.

2. STENCIL AND LABEL FOR SHIPMENT PER SK 118

1. MARKING FOR SHIPMENT AND STORAGE PER MIL-STD-129

NOTES:

1. TWO STEEL BANDS
1 1/2" TO 3/4" X 0.020
UNDER TOP PALLET BOARDS ONLY

28.5 IN X 28.5 IN
X 0.5 IN PLYWOOD

40 IN X 48 IN PALLET

48 IN MAX


4. FOR TRANSPORT OF DAMAGED OR DISCREPANT LITHIUM BATTERY. SEE SK 120

3. DEFINES ASSEMBLY FOR TRANSPORT EMPTY OR LOADED WITH
ACCEPTABLE LITHIUM BATTERY.

2. STENCIL AND LABEL FOR SHIPMENT PER SK 118

1. MARKING FOR SHIPMENT AND STORAGE PER MIL-STD-129

NOTES:



LOCK JAM NUT
USE 15/16" WRENCH

TORQUE COVER
CLAMP TO
50 ± 5 FT-LB
USE 15/16" WRENCH

VIEW
C-C

SECTION A - A
- I ILLUSTRATED


SECTION B-B

- PROVIDE 1/2" WIDE PLASTIC LIFTING STRAP AROUND (2)(3)(4)
 PROVIDE 1/2" WIDE PLASTIC LIFTING STRAP AROUND UPPER CUSHION
 ISOLATION SYSTEM PER APCA FAX DATED 9-14-94.
 FABRICATE FROM POLYETHYLENE FOAM PER PFP-C-17520
 -3- CONFIGURATION INCLUDES SIMULATED BATTERY FOR RAINFINDING
 -2- CONFIGURATION DOES NOT INCLUDE LITHIUM THIONYL CHLORIDE BATTERY
 -1- CONFIGURATION INCLUDES LITHIUM THIONYL CHLORIDE BATTERY
 CONDITION DRAW CONTENTS TO 0° F FOR SHIPMENT

rates =

[illegible]

APPENDIX 3
POLYETHYLENE CUSHION



APPENDIX 4
TEST PLAN/RESULTS



DEPARTMENT OF THE AIR FORCE

AIR FORCE MATERIEL COMMAND
WRIGHT-PATTERSON AIR FORCE BASE OHIO

MEMORANDUM FOR The Aerospace Corp.
2350 El Segundo Blvd.
El Segundo, Calif. 90245

FROM: AFMC-LSO/LGTP
5215 Thurlow Street
Wright-Patterson AFB OH 45433-5540

SUBJECT: Letter Report - 250AH Lithium Battery Fixture Handle Pull Test

1. Referencing telephone conversations between Dick Denno of Aerospace Corp. and Jason Gilreath of the Air Force Packaging Design Division, the Martin Marietta company felt the fixture handles were flimsy and would not satisfy a factor of safety of two (2) with a battery loaded in the fixture. Martin Marietta requested the Lexan handles be reinforced with aluminum plate in order to provide the needed strength.
2. A handle pull test was conducted to determine the acceptability of the existing handles. The 250AH Lithium Battery weighs 86 lbs. A test load of approximately 175 lbs would provide the required factor of safety of two (2). The first test consisted of a loaded fixture hanging free of support by both handles from a 2 inch wide cargo strap. The second test was to hang the loaded fixture by one single handle, also using a 2 inch wide cargo strap.
3. For both configurations, a lead test load of 600 lbs was used. This weight gives a factor of safety of approximately five (5) for two handles, and over ten (10) for a single handle. The maximum deflection when both handles were used was approximately 0.5" each (see figures 1 and 2). The maximum deflection for the single handle configuration was approximately 0.625" (see figures 3 and 4). In neither case did the handles fail or show signs of fracture.
4. Our point of contact is Mr. Jason Gilreath, at DSN 787-3362 or Comm (513) 257-3362, FAX 257-0231.

Leslie K. Clarke, III
Chief, AF Packaging Division

Attachment:

1. Figures 1 thru 4




Figure 1




Figure 2




Figure 3




Figure 4

APPENDIX 5
DISTRIBUTION LIST

DISTRIBUTION LIST

DTIC/FDAC CAMERON STATION ALEXANDRIA VA 22304-6145	1
HQ AFMC/LG WRIGHT-PATTERSON AFB OH 45433-5006	1
AFMC LSO/LO WRIGHT-PATTERSON AFB OH 45433-5006	1
AFMC LSO/LOP (LIBRARY) WRIGHT-PATTERSON AFB OH 45433-5540	10
HQ USAF/LGTT WASHINGTON DC 20330	1
654 ABG/LGT 7701 SECOND ST, STE 209 TINKER AFB OK 73145-9100	1
654 ABG/LGTP 7701 SECOND ST, STE 209 TINKER AFB OK 73145-9100	1
649 ABG/LGT BLDG 1135 7973 UTILITY DR HILL AFB UT 84056-5713	1
649 ABG/LGTP 7530 11th ST HILL AFB UT 84056-5707	1
651 ABG/LGT BLDG 1530 410 JACKSON RD KELLY AFB TX 78241-5312	1
651 ABG/LGTP 401 WISON BLVD KELLY AFB TX 78241-5340	1

DISTRIBUTION LIST (Cont'd)

652 ABG/LGT 1961 IDZOREK ST MCCLELLAN AFB CA 95652-1620	1
652 ABG/LGTP 1961 IDZOREK ST MCCLELLAN AFB CA 95652-1620	1
653 ABG/LGT BLDG 376 455 BYRON ST ROBINS AFB GA 31098-1860	1
653 ABG/LGTP BLDG 376 455 BYRON ST ROBINS AFB GA 31098-1860	1
ASC/AWL WRIGHT-PATTERSON AFB OH 45433	1
ASC/ALXS WRIGHT-PATTERSON AFB OH 45433-7642	1
ASC/YJA 110 WACISSA RD SUITE 15 EGLIN AFB FL 32542-5313	1
GSA OFFICE OF ENGINEERING MGT PACKAGING DIVISION WASHINGTON DC 20406	1
COMMANDER ATTN: N KARL (SUP 045) NAVAL SUPPLY SYSTEMS COMMAND WASHINGTON DC 20376-5000	1
COMMANDER ATTN: E PANIGOT (AIR 41212A) NAVAL AIR SYSTEMS COMMAND WASHINGTON DC 20361	1

DISTRIBUTION LIST (Cont'd)

COMMANDER 1
ATTN: T CORBE (CODE 8218)
SPACE AND NAVAL WARFARE SYSTEMS COMMAND
WASHINGTON DC 20360

ATTN: C MANWARRING (FAC 0644) 1
NAVAL FACILITIES ENGINEERING COMMAND
HOFFMAN BLDG 2 ROOM 12S21
ALEXANDRIA VA 22332

COMMANDING OFFICER 1
ATTN: K POLLOCK (CODE 15611K)
NAVAL CONSTRUCTION BATTALION CENTER
PORT HUENEME CA 93043

COMMANDER 1
NAVAL SEA SYSTEMS COMMAND
ATTN: G MUSTIN (SEA 66P)
WASHINGTON DC 20362

COMMANDER 1
ATTN: F BASFORD (SEA 05M3)
NAVAL SEA SYSTEMS COMMAND
WASHINGTON DC 20362

ATTN: E. H. BRIGGS (CODE 0512) 1
NAVAL AVIATION SUPPLY COMMAND
700 ROBBINS AVENUE
PHILADELPHIA PA 19111-5098

ATTN: F SECHRIST (CODE 0541) 1
NAVY SHIPS PARTS CONTROL CENTER
PO BOX 2020
MECHANICSBURG PA 17055-0788

COMMANDING OFFICER 1
ATTN: F MAGNIFICO (SESD CODE 9321)
NAVAL AIR ENGINEERING CENTER
LAKEHURST NJ 08733-5100

DISTRIBUTION LIST (Cont'd)

COMMANDING OFFICER NAVAL WEAPONS STATION EARLE NWHC/CODE 8023 COLTS NECK NJ 07722-5000	1
US AMC PACKAGING STORAGE AND CONTAINERIZATION CENTER/SDSTO-TE-E 16 HAP ARNOLD BLVD TOBYHANNA PA 18466-5097	1
DLSIE/AMXMC-D US ARMY LOGISTICS MGT CTR FT LEE VA 23801-6034	1
ATTN: Mike Ivankoe US ARMY ARDEC/SMCAR-AEP DOVER NJ 07801-5001	1
US ARMY NATICK LABS/STRNC-ES NATICK MA 01760	1
HQ AFMC/LGSH WRIGHT-PATTERSON AFB OH 45433	1
ASC/SDM WRIGHT-PATTERSON AFB OH 45433	1
ATTN: DLA-MMDO DEFENSE LOGISTICS AGENCY CAMERON STATION ALEXANDRIA VA 22304-6100	1
ATTN: DLA-AT DEFENSE CONTRACT MANAGEMENT COMMAND CAMERON STATION ALEXANDRIA VA 22304-6190	1
AGMC/DSP NEWARK AFS 43057-5000	1
AMARC/DST DAVIS MONTHAN AFB AZ 85707-5000	1

DISTRIBUTION LIST (Cont'd)

2750 TRANS/DMTT WRIGHT-PATTERSON AFB OH 45433-5001	1
HQ PACAF/LGTT HICKAM AFB HI 96853-5000	1
HQ USAFE/LGTT APO NEW YORK 09094-5000	1
HQ ACC/LGTT LANGLEY AFB VA 23665-5001	1
HQ AFSPACECOM/LKT PETERSON AFB CO 80914-5000	1
HQ ANGSC/LGTT ANDREWS AFB MD 20331-6008	1
HQ ATC/LGTT RANDOLPH AFB TX 78150-5001	1
HQ AU/LGTT MAXWELL AFB AL 36112-5001	1
HQ AMC/XONC SCOTT AFB IL 62225-5001	1
SCHOOL OF MILITARY PACKAGING TECHNOLOGY ATSZ-MP ABERDEEN PROVING GROUND MD 21005-5001	1
HQ USMC (CPP-2) WASHINGTON DC 20380	1
ATTN: DGSC/QED DEFENSE GENERAL SUPPLY CENTER 8100 JEFFERSON DAVIS HIGHWAY RICHMOND VA 23297-5000	1

DISTRIBUTION LIST (Cont'd)

ATTN: DGSC/OMAD 1
DEFENSE GENERAL SUPPLY CENTER
8100 JEFFERSON DAVIS HIGHWAY
RICHMOND VA 23297-5000

ATTN: DICK DENNO 1
M6/206
THE AEROSPACE CORPORATION
P. O. BOX 92957
LOS ANGELES, CALIFORNIA 90009

ATTN: MAJOR KEVIN KLONOSKI 1
2420 VELA WAY SUITE A5-1467
LOS ANGELES, CALIFORNIA 90245-4659

APPENDIX 6
REPORT DOCUMENTATION

REPORT DOCUMENTATION PAGE

Form Approved

OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)

2. REPORT DATE

25 Apr 95

3. REPORT TYPE AND DATES COVERED

Final Aug 94 - Mar 95

4. TITLE AND SUBTITLE

Development of Handling Frames and Shipping Containers for 250AH Lithium Thionyl Chloride Batteries

5. FUNDING NUMBERS

6. AUTHOR(S)

Jason Gilreath

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

AFPTF
AFMC LSO/LOP
Bldg. 70, Area C

8. PERFORMING ORGANIZATION
REPORT NUMBER

95-R-01

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

10. SPONSORING/MONITORING
AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release. Distribution is unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

This report is to document the design and fabrication of six shipping containers/assemblies for the 250AH Lithium Thionyl Chloride batteries manufactured by the Martin-Marietta Corporation in France. The handling frame is a combination of aluminum and GE Lexan. The cushion system is polyethylene foam, and the outer container is a UN-certified steel drum. The container passed a field test (shipment of a unit through the supply system). The containers were fabricated wholly in-house at the Air Force Packaging Technology & Engineering Facility.

14. SUBJECT TERMS

250 AH Lithium Thionyl Chloride batteries,
Lexan handling frame

15. NUMBER OF PAGES

14

16. PRICE CODE

17. SECURITY CLASSIFICATION
OF REPORT

Unclassified

18. SECURITY CLASSIFICATION
OF THIS PAGE

Unclassified

19. SECURITY CLASSIFICATION
OF ABSTRACT

Unclassified

20. LIMITATION OF ABSTRACT